

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations


Printing date: 11/04/2016

Revision: 11/04/2016

1 Identification

- **Product identifier**
- **Trade name:** SingleShot Wall Texture
- **Other product identifiers:** ETX Wall
- **Product code:** 3013
- **Recommended use and restriction on use**
- **Recommended use:** Textured coating
- **Restrictions on use:** See Sections 8 and 10 for further information.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
 ExperTexture
 170 Gemini Ave C-12
 Brea, CA
 USA
 (714)992-2276
- **Emergency telephone number:**
 ChemTel Inc.
 (800)255-3924, +1 (813)248-0585

2 Hazard(s) identification

- **Classification of the substance or mixture**
 Flam. Aerosol 2 H223 Flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Carc. 1A H350 May cause cancer. Route of exposure: Inhalation.
- **Label elements**
- **GHS label elements**
 The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**

 GHS02 GHS04 GHS08
- **Signal word:** Danger
- **Hazard statements:**
 H223 Flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H350 May cause cancer. Route of exposure: Inhalation.
- **Precautionary statements:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P211 Do not spray on an open flame or other ignition source.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/04/2016

Revision: 11/04/2016

Trade name: SingleShot Wall Texture

(Cont'd. of page 1)




P280 Wear protective gloves and eye protection.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

1317-65-3	limestone		30-50%
115-10-6	dimethyl ether	 Flam. Gas 1, H220  Press. Gas, H280	5-15%
14808-60-7	Quartz (SiO ₂)	 Carc. 1A, H350; STOT RE 1, H372	<1%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
 For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.
 Provide oxygen treatment if affected person has difficulty breathing.

· **After skin contact:**

Immediately rinse with water.
 If skin irritation is experienced, consult a doctor.

· **After eye contact:**

Remove contact lenses if worn, if possible.
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Unlikely route of exposure.
 Rinse out mouth and then drink plenty of water.
 Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed:**

Headache
 Breathing difficulty
 Coughing
 Frostbite

· **Danger:**

Danger of impaired breathing.
 May cause cancer by inhalation. Route of exposure: Inhalation.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/04/2016

Revision: 11/04/2016

Trade name: SingleShot Wall Texture

(Cont'd. of page 2)

- **Indication of any immediate medical attention and special treatment needed:**
Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Water fog / haze
Foam
Carbon dioxide
Gaseous extinguishing agents
Fire-extinguishing powder
- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Danger of receptacles bursting because of high vapor pressure if heated.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information:**
Eliminate all ignition sources if safe to do so.
If aerosols are bursting, stay clear until safe. Aerosol containers can be projectiles when bursting.
Cool endangered containers with water fog.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation.
Use personal protective equipment as required.
Keep away from ignition sources.
Protect from heat.
If containers are leaking, use respiratory protective device against the effects of fumes/dust/aerosol.
- **Environmental precautions** Avoid release to the environment.
- **Methods and material for containment and cleaning up**
Absorb liquid components with liquid-binding material.
Allow gas to dissipate.
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/04/2016

Revision: 11/04/2016

Trade name: SingleShot Wall Texture

(Cont'd. of page 3)

7 Handling and storage

- **Handling**

- **Precautions for safe handling:**

Use only in well ventilated areas.

Do not spray on flame or other ignition sources. No smoking.

Keep out of reach of children.

- **Information about protection against explosions and fires:**

Flammable aerosol.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Emergency cooling must be available in case of nearby fire.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

- **Conditions for safe storage, including any incompatibilities**

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Avoid storage near extreme heat, ignition sources or open flame.

Observe official regulations on storing packagings with pressurized containers.

- **Information about storage in one common storage facility:** Store away from foodstuffs.

- **Further information about storage conditions:**

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

1317-65-3 limestone

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust ** respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction

115-10-6 dimethyl ether

WEEL (USA)	Long-term value: 1000 ppm
EL (Canada)	Long-term value: 1000 ppm

14808-60-7 Quartz (SiO₂)

PEL (USA)	see Quartz listing
-----------	--------------------

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/04/2016

Revision: 11/04/2016

Trade name: SingleShot Wall Texture

(Cont'd. of page 4)

REL (USA)	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV (USA)	Long-term value: 0.025* mg/m ³ *as respirable fraction
EL (Canada)	Long-term value: 0.025 mg/m ³ ACGIH A2; IARC 1
EV (Canada)	Long-term value: 0.10* mg/m ³ *respirable fraction
LMPE (Mexico)	Long-term value: 0.025* mg/m ³ A2, *fracción respirable

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

- **Engineering controls:** No relevant information available.

- **Breathing equipment:**

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

Avoid release to the environment.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **Appearance:**

Form: Aerosol
Color: White

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/04/2016

Revision: 11/04/2016

Trade name: SingleShot Wall Texture

(Cont'd. of page 5)

· Odor:	Ether-like
· Odor threshold:	Not determined.
· pH-value:	8.8
· Melting point/Melting range:	Not applicable, as aerosol.
· Boiling point/Boiling range:	-28 °C (-18 °F)
· Flash point:	-43.5 °C (-46 °F) (Closed Cup)
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	350 °C (662 °F)
· Decomposition temperature:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
· Oxidizing properties:	Non-oxidizing.
· Vapor pressure:	100 kPa
· Density:	
Relative density:	1.34
Vapor density:	Not determined.
Evaporation rate:	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity	
Dynamic:	800 cPs
Kinematic:	Not determined.
VOC content:	98 g/L
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
Danger of receptacles bursting because of high vapor pressure if heated.
- **Possibility of hazardous reactions**
Develops readily flammable gases / fumes.
Reacts with oxidizing agents.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/04/2016

Revision: 11/04/2016

Trade name: SingleShot Wall Texture

(Cont'd. of page 6)

- **Conditions to avoid**
Excessive heat.
Store away from oxidizing agents.
- **Incompatible materials** Oxidizing agents
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** Based on available data, the classification criteria are not met.

- **IARC (International Agency for Research on Cancer):**

14808-60-7	Quartz (SiO ₂)	1
------------	----------------------------	---

- **NTP (National Toxicology Program):**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

- **Probable route(s) of exposure:**

Inhalation.
Eye contact.
Skin contact.

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Carc. 1A

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** May cause cancer by inhalation. Route of exposure: Inhalation.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:** Avoid release to the environment.

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/04/2016

Revision: 11/04/2016

Trade name: SingleShot Wall Texture



(Cont'd. of page 7)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Contact waste processors for recycling information.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---------------------|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1950 |
| · UN proper shipping name | |
| · DOT | Aerosols |
| · ADR, IMDG | AEROSOLS |
| · IATA | Aerosols, flammable |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 2.1 |
| · Label | 2.1 |
| · ADR | |
|  | |
| · Class | 2 5F Gases |

(Cont'd. on page 9)

Safety Data Sheet






acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/04/2016

Revision: 11/04/2016

Trade name: SingleShot Wall Texture

(Cont'd. of page 8)

· Label	2.1
· IMDG, IATA	
	
· Class	2.1
· Label	2.1
· Packing group	Aerosols are not assigned a packing group.
· Environmental hazards	
· Marine pollutant:	No
· Special precautions for user	Warning: Gases
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
 Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.	
· ADR	
 Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.	
· IMDG	
 Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.	
· IATA	
 Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.	

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/04/2016

Revision: 11/04/2016

Trade name: SingleShot Wall Texture

(Cont'd. of page 9)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

115-10-6	dimethyl ether	10000
----------	----------------	-------

· Proposition 65 (California)

· Chemicals known to cause cancer:

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

14808-60-7	Quartz (SiO ₂)	1
------------	----------------------------	---

· NIOSH-Ca (National Institute for Occupational Safety and Health):

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 11/04/2016

Revision: 11/04/2016

Trade name: SingleShot Wall Texture

(Cont'd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 11/04/2016 / -

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

LDLo: Lowest Lethal Dose Observed

Flam. Gas 1: Flammable gases – Category 1

Flam. Aerosol 2: Aerosols – Category 2

Press. Gas: Gases under pressure – Compressed gas

Carc. 1A: Carcinogenicity – Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com